

Trans-Kote® PET/MR Laminating Film

DESCRIPTION:

Trans-Kote® PET/MR Laminating Film is a clear polyester base film with a low melt adhesive

CHARACTERISTICS:

- Water, oil, acid, and alkali resistant.
- Can be die cut.

TECHNICAL DATA:

PROPERTIES	UNIT	75/60	92/60	ASTM
THICKNESS ±10%	inches	.00135	.00152	D 2103
YIELD	ln ² /lb	17,274	15,051	D 4321
SURFACE TENSION – adhesive side	dynes/cm	44 - 56		D 2578
TENSILE STRENGTH ±10%	MD	psi	18,100	D 882
	TD	psi	16,600	
SHRINKAGE	MD	%	1.2 – 2.0	150c/30min
	TD	%	0.5 – 1.0	

*All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 9/30/2016

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM

© 2016 Transcendia Inc. All Rights Reserved.