

Transalloy® P-300 Multi-Polymer Alloy

DESCRIPTION:

Transalloy® P-300 is an especially multi-polymer material formulated for durability, high tear resistance and excellent impact strength for the most demanding applications. The surface of P-300 is specifically engineered to provide superior performance on and off the press. Transalloy® P-300 can be used in point of purchase displays, in-store signage, outdoor displays, horticultural signage/tags, thermoformed trays and promotional items.

CHARACTERISTICS:

- Can be printed Offset Lithography, Screen, UV Digital and Flexography
- Can be heat bent, folded, die cut, punched, thermoformed and guillotine cut
- Excellent dimensional stability
- Provides good toughness, stiffness and impact strength
- Available in sheets or rolls
- Available in a variety of opacities from natural to dead opaque
- Corona treatment or UV Inhibitors available upon request
- Surfaces include satin/matte, ultra-gloss/matte
- Recycle Code #6

TECHNICAL DATA:

PROPERTIES	UNIT	TYPICAL VALUES	TEST METHOD
THICKNESS ± 5% or .001 Maximum (whichever is greater)	inches	.010" TO .050"	T 411
YIELD @ .020	ln ² / lb	1300	T410
SPECIFIC GRAVITY @ .020	g/cm ³	1.03	D 1505
TENSILE STRENGTH @ .020 @ BREAK	MD	2600	D 882
	TD	2700	
ELONGATION @ .020 @ BREAK	MD	170%	
	TD	290%	
TEAR RESISTANCE @ .020 INITIATED	MD	1.1	D 1938
	TD	1.3	
TEAR RESISTANCE @ .020 UNINITIATED	MD	6.6	D 1004
	TD	7.5	
STIFFNESS @ .020	MD	64	D 5342
	TD	84	
WETTING TENSION - minimum	Dyne/cm ²	40	T698

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty no15375r guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 9/22/2016

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM

© 2016 Transcendia Inc. All Rights Reserved.