

TRANS-SEALING® FLO-6APET

DESCRIPTION:

TRANS-SEALING-FLO-6APET is a heat sealable lidding film with a specialty sealant on a PET substrate designed for tight to lock seal of a variety of trays. This film is laminated to a 92 GA PET top layer.



CHARACTERISTICS:

- Good moisture and oxygen barrier
- One side sealable
- Tight, lock seal to PET substrates

TECHNICAL DATA:

PROPERTIES	UNIT OF MEASURE	PROPERTY VALUE	TEST METHOD
PHYSICAL			
Thickness	Gauge	2.2 mil	
Yield	in ² /lb	9,200	
COF Sealant side		0.3	ASTM D1894
Heat resistant side		0.55	
BARRIER			
MVTR	g/100 in ² /day	0.5	ASTM F1249
OTR	Cc/100 in ² /day	3.30	ASTM D3985 23°C, 0%RH
THERMAL			
Shrink			
MD	%	1.7	ASTM D1204
TD	%	0.3	ASTM D 1204

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 10/13/2017

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM

© 2017 Transcendia Inc. All Rights Reserved.