

DIGIKOTE® Matte Laminating Film

DESCRIPTION

DIGIKOTE Matte is a 3-mil, low melt, thermally activated laminating film especially designed for applications that require enhanced glare reduction. It is ideal for trade show graphics and point of purchase displays.

CHARACTERISTICS

Low-melt adhesive

Provides more glare reduction than standard satin films

• Water, oil, acid, and alkali resistant

• Can be die cut

Slit Widths Available: 25", 38", 43", 51", 55", 62"

Length Available: 500'

FDA STATUS

Manufactured with materials compliant with FDA regulations.

COMPLIANCE

Please visit https://www.transcendia.com/compliance for more compliance information.

TECHNICAL DATA

PROPERTY		UNIT OF MEASURE	TYPICAL VALUE	TEST METHOD
Thickness		inches	0.003	ASTM D2103
Yield		in²/lb	9,110	ASTM D4321
COF, base film (Kinetic)		-	0.45-0.55	ASTM D1894
Surface Tension (adhesive side)		dyne/cm	52-54	ASTM D2578
Tensile Strength	MD	psi	5,300	ASTM D882
Tensile Strength	TD	psi	6,000	ASTM D882
Elongation	MD	%	110	ASTM D882
Elongation	TD	%	90	ASTM D882
Laminating Temperature Range (Internal)		°F	185-195	-
Bond Strength (laminated to itself)		lb/in	10	ASTM F88

^{*}All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.