

CLASSICVUE DO-ALLINER

EXTERIOR MOUNT D.O.T.-COMPLIANT ONE-WAY VISION FILM WITH OUR PATENTED DO-ALLINER FOR UNIVERSAL PRINTING

Perfect for Vehicle Window Graphics

Exterior-mount window graphics for buses and other vehicles, bus shelters, retail signage, event centers and a wide variety of other applications. ClassicVue Do-Alliner's smaller perforation diameter and 50/50 pattern make it ideal for vehicle/fleet window graphics.



Specifications

- 8 mil. black/white laminated PVC-based film
- .06 in. (1.5 mm) perforation diameter
- Perforation pattern: ~ 50/50 (50% open)
- Film: 8 mil. calendered PVC on a 3 in. core
- Standard roll sizes:
 - 54 in. x 25 ft.
 - 54 in. or 60 in. x 100 ft. or 1000 ft.

Applications

- Buses
- Commercial Signage
- Fleet Vehicles
- Transportation Shelters
- Retail Signage
- Point of Purchase

**Certified for
HP Latex Inks**

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at:
hp.com/go/mediasolutionslocator

Features & Benefits

- Exterior Mount
- Engineered to maintain exterior graphic quality for up to 3 years
- Compliant with D.O.T. requirements of 1.5 mm perforation diameter and 50/50 perforation pattern for use on vehicles
- Simple to apply
- Easy to remove
- Compatible with Latex, UV, Eco-solvent, Screen and UV Offset Printing
- Certified and Profiled on HP® Latex 300, 630W, 700/800W, 3000 and R Series Printers
- Constructed with our patented Do-Alliner for universal printing*



*U.S. Patents 7,897,239 and 8,211,527



Transcendia
A Leader in Custom and Engineered Films



CLASSICVUE DO-ALLINER

Exterior Mount Product Specifications

Product Code: CFEABW

Certified for
HP Latex Inks

Features	Description
Applications	Windows, glass doors and other transparent, non-porous surfaces.
Composition	White/black PVC laminate with clear pressure-sensitive adhesive coating and our patented DO-ALLINER for universal printing, laminated to perforated paper to absorb ink.
Open Area	~50%
Vinyl Thickness Including Adhesive	~8 mil. .008 in. 203 microns
Release Liner Thickness	~7 mil. .007 in. 178 microns
Adhesive Thickness	~1 mil. .001 in. 25 microns
Perforation Diameter	.060 in. (1.5 mm)
Standard Widths & Lengths	54 in. or 60 in. x 100 ft. or 1000 ft. (137 cm or 152 cm x 30.48 m or 304.8 m) 54 in. x 25 ft. (137 cm x 7.62 m) Custom sizes available by special order.
Dimensional Stability	Good
Minimum Application Temperature	40°F (4°C)
Service Temperature Range	0°F to 140°F (-17°C to 60°C)
Expected Lifetime Exterior	3 years. 6 months for clean removal. Adhesion may increase with time.
Water Resistance	Fair. Immersion in water not recommended. If exposure to rain is anticipated, a compatible, optically clear overlaminate can be used to prevent holes from filling with water.
Humidity Resistance	Fair
Solvent Resistance	Good
Storage Stability	1-year shelf life when stored at 70°F (21°C) and 50% relative humidity
Colors Available	White on print side and black on adhesive side.
Printing	Use standard vinyl inks. Print image on vinyl side, not on release liner. Compatible with Latex, UV, Eco-Solvent, Screen and UV Offset Printing. Certified and Profiled on HP Latex 300, 630W, 700/800W, 3000 & R Series Printers
Application	Apply to clean, dry glass surface. Use mild soap & water, rinse & dry glass well. Do NOT use ammonia, Windex® or other solvent-based glass cleaner prior to application.
Removal	Six months for clean removability.

It is the responsibility of purchasers to independently verify the suitability of the products for their specific applications and print methods prior to use. Transcendia, Inc. cannot be held liable for any misuse, damage or losses as specified in its product warranty.



Contact us | To speak with an print specialist call **800-745-5802 (US), 800-268-4108 (CAN)**
or visit **transcendia.com/contact-us**

