

# IMAGEVUE DO-ALLINER

EXTERIOR MOUNT HIGH RESOLUTION  
PERFORATED PVC FILMS WITH PATENTED  
DO-ALLINER FOR UNIVERSAL PRINTING

## Finer Resolution

Clear Focus ImageVue® Do-Alliner® films have a 65/35 perforation pattern that provides more print surface area making them ideal for graphics with small details and text that require a finer resolution.



## Specifications

- 8 mil. black/white laminated PVC-based film
- .06 in. (1.5 mm) perforation diameter
- Perforation pattern: ~65/35 (35% open)
- Standard roll sizes:
  - 54 in. x 25 ft.
  - 54 in. or 60 in. x 100 ft. or 1000 ft.

## Applications

- Small-format & graphics-intensive window signage
- Decals
- Point of Purchase
- Retail Signage
- Commercial Signage
- Not recommended for vehicle graphics due to reduced visibility

**Certified for  
HP Latex Inks**

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at:  
[hp.com/go/mediasolutionslocator](http://hp.com/go/mediasolutionslocator)

## Features & Benefits

- Exterior Mount
- Engineered to maintain exterior graphic quality for up to 3 years
- High print area is perfect for small- and medium-format window graphics
- Engineered to maximize resolution to showcase small details and text
- Simple to apply
- Compatible with Latex, UV, Eco-solvent, Screen and UV Offset Printing
- Certified and Profiled on HP® Latex 300, 630W, 700/800W, 3000 and R Series Printers
- Constructed with our patented Do-Alliner for universal printing\*



\*U.S. Patents 7,897,239 and 8,211,527



**Transcendia**  
A Leader in Custom and Engineered Films



# IMAGEVUE DO-ALLINER

## Exterior Mount Product Specifications

Product Code: CFEABWIV

Certified for  
HP Latex Inks

Features	Description
<b>Applications</b>	Windows, glass doors and other transparent, non-porous surfaces.
<b>Composition</b>	White/black calendered PVC film with clear pressure-sensitive adhesive coating and our patented DO-ALLINER for universal printing laminated to perforated paper to absorb ink.
<b>Open Area</b>	~35%
<b>Perforation Diameter</b>	.06 in. (1.5 mm)
<b>Vinyl Thickness Including Adhesive</b>	~8 mil.   .008 in.   203 microns
<b>Release Liner Thickness</b>	~7 mil.   .007 in.   178 microns
<b>Adhesive Thickness</b>	~1 mil.   .001 in.   25 microns
<b>Standard Widths &amp; Lengths</b>	54 in. or 60 in. x 100 ft. or 1000 ft. (1.37 cm or 1.52 cm x 30.48 m or 304.8 m) 54 in. x 25 ft. (1.37 cm x 7.62 m) Custom sizes available by special order.
<b>Dimensional Stability</b>	Good
<b>Minimum Application Temperature</b>	40°F (4°C)
<b>Service Temperature Range</b>	0°F to 140°F (-17°C to 60°C)
<b>Expected Lifetime Exterior</b>	Up to 3 years. 6 months for clean removal. Adhesion may increase with time.
<b>Water Resistance</b>	Fair. Immersion in water not recommended. If exposure to rain is anticipated a compatible, optically clear overlaminate can be used to prevent holes from filling with water.
<b>Humidity Resistance</b>	Fair
<b>Solvent Resistance</b>	Good
<b>Storage Stability</b>	1 year shelf life when stored at 70°F (21°C) and 50% relative humidity
<b>Colors Available</b>	White on print side and black on adhesive side.
<b>Printing</b>	Print image on vinyl side, not on release liner side. Compatible with Latex, UV, Eco-Solvent, Screen and UV Offset Printing. Certified and Profiled on HP Latex 300, 630W, 700/800W, 3000 & R Series Printers
<b>Application</b>	Apply to clean, dry glass or other non-porous surface. Use mild soap and water, rinse and dry glass well. Do NOT use ammonia, Windex® or other solvent-based glass cleaner prior to application. Not for use on vehicle windows due to reduced visibility.
<b>Removal</b>	Six months for clean removability.

It is the responsibility of purchasers to independently verify the suitability of the products for their specific applications and print methods prior to use. Transcendia, Inc. cannot be held liable for any misuse, damage or losses as specified in its product warranty.



Contact us | To speak with a print specialist call **800-745-5802 (US), 800-268-4108 (CAN)**  
or visit **[transcendia.com/contact-us](https://transcendia.com/contact-us)**

