



# **BIOTECT® VCI ANTI-CORROSION FILM**

### DESCRIPTION

MetPro<sup>®</sup> BioTect VCI Anti-Corrosion Film is impregnated with MetPro's proprietary, all natural BioTect masterbatch material, which is a vapor and contact corrosion inhibitor formulation recommended for ferrous and non-ferrous metals such as steel, aluminum, iron, copper, and galvanized steel. MetPro BioTect VCI Anti-Corrosion Films are amine-, nitrite- and benzotriazole- free making it a safe option for the environment and employees.

#### CHARACTERISTICS

- Amine-, nitrite- and benzotriazole- free
- Available in multiple formats including film, sheets, bags, rolls and tubing.
- Low density polyethylene (LDPE) carrier
- Low order
- Color as required.
- Contains no heavy metals.
- Percent of solids is 100%.
- Density of 0.90-1.00g/cm<sup>3</sup>
- Contains no heavy metals.
- Also available in mil thicknesses of 1.5 mil. to 10 mil.

#### **FDA STATUS**

Manufactured with materials compliant with FDA regulations.

#### COMPLIANCE

Please visit <u>https://www.transcendia.com/compliance</u> for more compliance information.

## **TECHNICAL DATA**

| PROPERTIES             | UNIT OF MEASURE | TYPICAL VALUES | TEST METHOD                             |
|------------------------|-----------------|----------------|---|
| Thickness (+/-) 10%    | gauge           | 4 mil.         | In accordance with BFSV-<br>TL8135-0043 |
| Tensile Strength MD    | psi             | 9282           | ASTM D882                               |
| Tensile Strength TD    | psi             | 6672           | ASTM D882                               |
| Tear Strength          | g               | 149 -1164      | ASTM D882                               |
| Elongation at Break MD | %               | 390            | ASTM D882                               |
| Elongation at Break TD | %               | 650            | ASTM D882                               |
| Dart Drop Impact       | g/mil.          | 230            | ASTM D1709A                             |
| Storage                | months          | 24             | -                                       |

Testing for special metals such as cadmium, nickel and alloys is recommended.

\*All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.