

TRANSPROP™ CPPHS-F

DESCRIPTION:

TransProp™ CPPHS-F is a high slip cast polypropylene film produced from homo-polymer PP resins.

CHARACTERISTICS:

- High slip
- Good stiffness and temperature resistance

FDA STATUS:

Manufactured with materials compliant with FDA regulations.

TECHNICAL DATA:

PROPERTIES	UNIT OF MEASURE	TYPICAL VALUES	TEST METHOD
Thickness	Gauge	100	-
Yield	in ² /lb	30,800	-
Tensile Strength MD	lb/in ²	7000	ASTM D 882
Tensile Strength TD	lb/in ²	5500	ASTM D 882
Elongation at Break MD	%	550	ASTM D 882
Elongation at Break TD	%	750	ASTM D 882
Haze	%	>3.5	ASTM D 1003
Gloss (45°)	G.U.	75	ASTM D 2457
Coefficient of Friction	GRMS	.18	ASTM D1894
Secant Modulus MD	Psi	115,000	ASTM D882
Secant Modulus TD	Psi	110,000	ASTM D882

*All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 9/28/2016

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM