

Clear Laser-Printable Index Tabbing Film 2.5

DESCRIPTION:

Clear Laser-Printable Index Tabbing Film 2.5 is a clear laser print receptive polyester-based tabbing film with a low melt adhesive.

CHARACTERISTICS:

- Water, oil, acid, and alkali resistant.
- Can be die cut.

Standard Width(s):

1.625" /41.3mm

TECHNICAL DATA:

PROPERTIES	UNIT	2.5 mil	ASTM
Finish		GLOSS	
THICKNESS $\pm 10\%$	inches	.0025	D 2103
	mm	.0635	
YIELD	yd ² /lb	6.5	D 4321
	m ² /kg	12.0	
FINISHED WEIGHT	lb/yd ²	.153	D 2578
	kg/m ²	.083	
SURFACE TENSION – adhesive side	dynes/cm	44 – 54	D 882
TENSILE STRENGTH $\pm 10\%$	MD	psi	24,000
		kg/cm ²	1,659
	TD	psi	28,800
		kg/cm ²	1,930
ELONGATION	MD	%	140
	TD	%	110
LAMINATING TEMPERATURE RANGE	°F	170 – 220	
	°C	77 – 104	
BOND STRENGTH - self	lbf/in	4 – 7	
	N/cm	7 – 12	

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 10/24/2016

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM