

# Color Laser-Printable Index Tabbing Film 2.5

## DESCRIPTION:

Color Laser-Printable Index Tabbing Film 2.5 is a color tinted laser print receptive polyester-based tabbing film with a low melt adhesive.

## CHARACTERISTICS:

- Water, oil, acid, and alkali resistant.
- Can be die cut.

## Standard Width(s):

1.625"/41.3mm

## Standard Colors:

Blue, Green, Gray, Red, Yellow  
 Custom colors available

## TECHNICAL DATA:

PROPERTIES	UNIT	2.5 mil	ASTM	
Finish		GLOSS		
THICKNESS $\pm 10\%$	inches	.0025	D 2103	
	mm	.0635		
YIELD	yd <sup>2</sup> /lb	6.5	D 4321	
	m <sup>2</sup> /kg	12.0		
FINISHED WEIGHT	lb/yd <sup>2</sup>	.153		
	kg/m <sup>2</sup>	.083		
SURFACE TENSION – adhesive side	dynes/cm	44 – 54	D 2578	
TENSILE STRENGTH $\pm 10\%$	MD	psi	24,000	D 882
		kg/cm <sup>2</sup>	1,659	
	TD	psi	28,800	
		kg/cm <sup>2</sup>	1,930	
ELONGATION	MD	%	140	D 882
	TD	%	110	
LAMINATING TEMPERATURE RANGE	°F	170 – 220		
	°C	77 – 104		
BOND STRENGTH - self	lbf/in	4 – 7		
	N/cm	7 – 12		

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 10/24/2016

**CORPORATE HEADQUARTERS** 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

**TRANSCENDIA.COM**