

ProPrint® ClingMate®

DESCRIPTION:

ProPrint® ClingMate® is a highly printable, rigid polypropylene sheet with a high performance ultra-removable adhesive (URA) back. It is a high tear resistant media that has been specially formulated for point of purchase displays that require clean removability of adhesive products for up to 12 months indoors.

CHARACTERISTICS:

- Easily printed using offset lithography, UV digital and screen printing.
- Can be applied to most clean, non-porous surfaces: metal, polypropylene, stainless steel, painted metal and glass.
- Available in sheets and rolls
- Great for decorative decals, product identification tags and point of purchase displays for appliances
- Can be applied by normal wet application methods

TECHNICAL DATA:

Typical physical properties	
THICKNESS	.008 ProPrint face film .001 Ultra-removable Adhesive (URA) .007 liner
OPACITY	1.5
YIELD n ² /lb	1431
TENSILE STRENGTH PSI +/- 10%	MD 3400 TD 0000
ELONGATION	MD 550% TD 500%
TEAR RESISTANCE - INITIATED	MD 1 lbs TD 4 lbs
TEAR RESISTANCE - UNINITIATED	MD 6.4 lbs TD 8.0 lbs
MINIMUM APPLICATION TEMPERATURE	+50° F
SERVICE TEMPERATURE RANGE	-40°F to +180°F
ADHESION	PSTC -1 with 24 hour dwell at room temperature

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 10/25/2016

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM

© 2016 Transcendia Inc. All Rights Reserved.