



## Stick-Mate<sup>™</sup> Permanent Adhesive Vinyl

## **DESCRIPTION:**

Stick-Mate<sup>™</sup>, a Transilwrap Trans-Cling<sup>™</sup> product, is a pressure sensitive vinyl on a 90# liner. It has an agressive, high tack, permanent adhesive. Stick-Mate<sup>™</sup> is available top coated and non-top coated, clear or white, in 20"x 27" & 27"x 38"sheets and 54" x 750' rolls for sheeting.

## CHARACTERISTICS:

- Stick-Mate<sup>™</sup> is excellent for indoor and outdoor use, especially transit advertising applications.
- Excellent for bumper stickers, P-O-P decals, and product markings.
- Can be printed using conventional or UV inks for flexo, offset, or screen process printing.
- Good dimensional stability and two year shelf life under proper storage conditions.

## TECHNICAL DATA:

PROPERTIES	TYPICAL VALUES	TEST METHOD
THICKNESS	3.4 mil film; 4.2-4.6 mils with adhesive	
APPLICATION TEMPERATURE	+ 40° F Min.	
SERVICE TEMPERATURE	-40° F to +200° F	
SURFACE FINISH	Gloss	
ADHESION	40 oz./in. (to stainless steel)	PSTC method #1
WATER RESISTANCE	Not recommended where immersed.	
HUMIDITY RESISTANCE	Fair	
EXPECTED EXTERIOR EXPOSURE	2 Years	
STORAGE STABILITY	2 YR. @ 70° F and 50% relative humidity	

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131 USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax