

Trans-Kote® Ultraburst Laminating Film

DESCRIPTION:

Trans-Kote® Ultraburst film is a high clarity, abrasion-resistant polyester-based film designed for high speed single and double-sided laminating.

CHARACTERISTICS:

- Ideal for book jackets, posters, menus, maps and commercial applications demanding excellent clarity and protection
- Available as a high-gloss film
- Low melt point adhesive
- Water, oil, acid, alkali-resistant
- Can be die cut when laminated

TECHNICAL DATA:

PROPERTIES	UNIT OF MEASURE	TYPICAL VALUE	TEST METHOD
Thickness	Gauge	120	Transcendia Test
Yield	in ² /lb	20,750	Transcendia Test
Tensile Strength MD	psi	11,000	ASTM D882A
Tensile Strength TD	psi	12,250	ASTM D882A
Elongation at Break MD	%	115	ASTM D882A
Elongation at Break TD	%	90	ASTM D882A
Surface Tension (dyne) - adhesive	dyne	44-52	ASTM D2578
Laminating Temperature	°F	210-230	
Bond Strength (to self)	pli	5 - 7	

*All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 9/22/2016

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM