

# REAL PEEL® RP11 V0-TABBED CAP LINER

## DESCRIPTION:

Real Peel® is a one piece easy-open pull tab laminate designed for induction sealing cap liners. This robust, multi-layer structure provides a clean peel and excellent hermetic seal to PET, HDPE, and PP containers.

## CHARACTERISTICS:

- Easy-open pull tab design
- Excellent cutting and lining characteristics
- Broad sealing operating window
- Hermetic seal
- Great moisture and gas barrier
- Prevents leaks

## FDA STATUS:

- Manufactured with materials compliant with FDA regulations
- Produced in accordance with GMPs

## Product Construction



## TECHNICAL DATA:

PROPERTIES	UNIT OF MEASURE	TYPICAL VALUE		TEST METHOD
		In Areas	In Areas	
		Excluding Tab	Including Tab	
Total Thickness	Inches	0.0085	0.0118	D6988-08
Aluminum Foil Thickness	Inches	0.001	0.001	D6988-08
Water Vapor Permeability	g/100 sq. in/24hr	< 0.01	< 0.01	D3985-81
Oxygen Permeability	cc/100 sq. in/24 hr.	< 0.01	< 0.01	F1249-90
Tensile Strength MD	Psi	13,850	-	D882
Elongation at Break MD	%	115	-	
90° Peel Peel Resistance to PET 38 mm cap RF Dwell 0.7-1 sec	lbf.	5-10		Using Handheld Induction Sealer at "High" Intensity Setting Applied Downward Torque = 21-24lbs.
90° Peel Peel Resistance to HDPE 38 mm cap RF Dwell 0.6-1 sec		9-14		
90° Peel Peel Resistance to PP 38 mm cap RF Dwell 0.6-1 sec		8-11		

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 11/13/2017

**CORPORATE HEADQUARTERS** 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

[TRANSCENDIA.COM](http://TRANSCENDIA.COM)

© 2017 Transcendia Inc. All Rights Reserved.

