

# TRANS-KOTE® ULTIMATTE Nylon™

## DESCRIPTION:

TRANS-KOTE® ULTIMATTE Nylon™ is a nylon based film, engineered with our durable, ULTIMATTE coating that delivers a luxurious matte finish to any application.

## CHARACTERISTICS:

- ULTIMATTE surface
- Exceptional anti-curl / lay-flat for single side lamination
- Accepts print / glue / foil stamping
- Water, oil, acid, and alkali resistant
- Can be die cut.

## TECHNICAL DATA:

PROPERTY	UNIT OF MEASURE	PROPERTY VALUE	TEST METHOD
Thickness	Gauge	.00130	F 2251
Yield	in <sup>2</sup> /lb	20,850'	D 4321
Surface Tension – adhesive side	dynes/cm <sup>2</sup>	44 - 52	D 2578
Coefficient Of Friction (base film side)	kinetic	0.40 – 0.60	D 1894
Tensile Strength			
MD	Psi	13,100	D882
TD		12,600	
Elongation			
MD	%	75	D882
TD		80	
Lamination Temperature	°F	200-220	-
Bond Strength	lb/in	4-6	D1876

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 02/13/2018

**CORPORATE HEADQUARTERS** 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

[TRANSCENDIA.COM](http://TRANSCENDIA.COM)

© 2017 Transcendia Inc. All Rights Reserved.