


WalkerTalker® Vinyl Base Component*

DESCRIPTION:

The WalkerTalker® floor graphics printable component is a white, vinyl film with a removable pressure sensitive adhesive and a 90 lb. release liner. The surface is treated to provide adhesion for various printing inks. The acrylic removable adhesive is specifically designed for high performance removable applications.



CHARACTERISTICS:

- Excellent slip resistance, passed UL 410 "Floor Coating and Finishing Material" (slip resistance only when used as part of WalkerTalker® system).
- Excellent anti-curl properties assure economical performance through printing and coating operations.
- Water, oil, acid, and alkali resistant.
- Excellent UV stability and resistance to thermal aging.
- Easy stripping liner with minimal adhesive "pick".
- Can be die-cut.
- Printable using offset, screen, digital screen and flexo processes

TECHNICAL DATA:

PROPERTIES		TYPICAL VALUES	TEST METHOD
Thickness - Vinyl Facestock		0.0035"	
Thickness - Adhesive		0.001"	
Thickness - Liner		0.0068"	
Adhesion	Stainless Steel	0.30 lbs/in Nominal 180° peel @ 20 min. dwell	PSTC1 Modified
		1.0 lbs/in Nominal 180° peel @ 24 hr. dwell	
	Industrial Vinyl Tile	0.25 lbs/in Nominal 180° peel @ 20 min. dwell	
		0.5 lbs/in Nominal 180° peel @ 24 hr. dwell	
Liner Release - T-Peel @ 30cm/min		25 gm/in	PSTC4 Modified
Yield		2200 sq. in/lb	


Note: All information and recommendations should be used as a guide and not for specification purposes. Furnishing this information does not constitute a warranty. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Users shall assume all risks resulting from the use of our products and must confirm adaptability thereof by their own tests. Liability will in no event exceed value of the material sold.

* WalkerTalker® Vinyl Base Component is only sold as a companion to WalkerTalker® overlaminating components.

WalkerTalker® Overlaminates*

DESCRIPTION:

The WalkerTalker® floor graphics overlaminates component is a scratch resistant film with a water-clear permanent pressure sensitive adhesive. The overlaminates is a calendared film processed to provide a satin (mar resistant) first surface. The acrylic adhesive used has been formulated for high tack and high peel adhesion.



CHARACTERISTICS:

- Excellent slip resistance, passed UL 410 "Floor Coating and Finishing Material" (slip resistance only when used as part of WalkerTalker® system).
- Excellent UV stability and resistance to thermal aging.
- Easy stripping liner with minimal adhesive "pick".
- Superior scratch resistance and wear.
- Water, oil, acid, and alkalai resistant.
- Can be die-cut.

TECHNICAL DATA:

PROPERTIES	TYPICAL VALUES		TEST METHOD
Thickness - Vinyl Facestock	0.006"	0.008"	
Thickness - Adhesive	0.0018" nominal	0.0018" nominal	
Thickness - Liner	0.002"	0.002"	
Adhesion - Stainless Steel	4.0 lbs/in Nominal 180° peel @ 20 min. dwell	4.0 lbs/in Nominal 180° peel @ 20 min. dwell	PSTC1 Modified
	8.0 lbs/in Nominal 180° peel @ 24 hr. dwell	8.0 lbs/in Nominal 180° peel @ 24 hr. dwell	PSTC1 Modified
Liner Release	4 gm/in nominal	4 gm/in nominal	PSTC4 Modified
Yield	1987 sq in/lb	1987 sq in/lb	

Note: All information and recommendations should be used as a guide and not for specification purposes. Furnishing this information does not constitute a warranty. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Users shall assume all risks resulting from the use of our products and must confirm adaptability thereof by their own tests. Liability will in no event exceed value of the material sold.

* WalkerTalker® Overlaminates is only sold as a companion to WalkerTalker® base components.