

TRANS-KOTE® SCUFF RESISTANT MATTE PET/MR

Protective & Aesthetic

DESCRIPTION:

Trans-Kote® Scuff Resistant Matte PET/MR laminating film is a high clarity, polyester-base film designed for high speed laminating. The Scuff Resistant Matte coating provides a luxurious, haptic soft feel to any application. The SRM coating also provides more resistance to scuffing than standard matte films. This film also has a specially formulated co-polymer adhesive for a low melt point lamination.

CHARACTERISTICS:

- Haptic, soft feel
- Accepts spot UV & foil stamping
- Enhances overall durability and appearance of graphics
- Can be die cut
- Water, oil, acid and alkali resistant

TECHNICAL DATA:

PROPERTIES		1.3	1.7	3.0	5.0	ASTM
THICKNESS ±10%		.0013"	.00170"	.00300"	0.00500"	
SURFACE TENSION - dyne - adhesive side		44 to 52				
COEFFICIENT OF FRICTION OF BASE FILM SIDE		0.45 to 0.55				D 1894
TENSILE STRENGTH - psi ±10%	MD	12,100	9,235	5,235	5,800	D 882
	TD	12,600	9,640	5,460	6,100	
ELONGATION - %	MD	100	100	100	100	D 882
	TD	95	95	95	95	
YIELD - in2/lb		19,130	15,170	9,355	5,650	
LAMINATING TEMPERATURE RANGE - °F - internal		210 to 230				
BOND STRENGTH - p/i - laminated to itself		5 to 7	6 to 8	7 to 9	10	

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Order today, call us at 800-972-8858 or 847-678-1800
Send us your request at [TRANSCENDIA.COM/CONTACT-US](https://www.transcendia.com/contact-us)