

TRANSPETG™ SHRINK SLEEVE 05A

DESCRIPTION:

TransPETG Shrink Sleeve 05A is a heat shrinkable film combining high overall shrinkage and excellent printability.

CHARACTERISTICS:

- Suitable for a wide variety of shapes due to its toughness and shrinkage character
- Anti-static coated on one side

TECHNICAL DATA:

PROPERTIES	UNIT OF MEASURE	TYPICAL VALUE	TEST METHOD
Thickness	Gauge	200	
Yield	In ² /lb	10,733	
Tensile Strength MD	psi	8,730	ASTM D882A
Tensile Strength TD	psi	28,650	ASTM D882A
Elongation at Break MD	%	562	ASTM D882A
Elongation at Break TD	%	36	ASTM D882A
Elmendorf Tear Strength MD	g/ply	180	ASTM D1922
Elmendorf Tear Strength TD	g/ply	19	ASTM D1922
Haze	%	4.3	ASTM D1003
Shrinkage Stress	MPA	9.5	-
Specific Gravity	-	1.31	-
Coefficient of Friction	-	0.26	ASTM D1894
Ring Crush		8.2	TAPPI T818

*All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 09/28/2016

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM

© 2016 Transcendia Inc. All Rights Reserved.