

TRANSTWIST™ PVC

DESCRIPTION:

TransTwist PVC is a clear PVC twist wrap film suitable for packaging various food products.

CHARACTERISTICS:

- Antistatic
- Excellent retention of twist
- Easily printed without any treatment
- High clarity and gloss

FDA STATUS:

Manufactured with materials compliant with FDA regulations.

TECHNICAL DATA:

PROPERTIES	UNIT OF MEASURE	TYPICAL VALUE	TEST METHOD
Thickness	Gauge	120	-
Yield	in ² /lb	16,768	-
Yield Variation	%	<+/-4	-
Tensile Strength MD	KG/CM ²	650-800	D882
Tensile Strength TD	KG/CM ²	600-700	D882
Elongation at Break MD	%	100-190	D882
Elongation at Break TD	%	100-200	D882
Coefficient of Friction	Static	0.20-0.40	D2570
Coefficient of Friction	Dynamic	0.18-0.30	D2570
Impact Resistance	KG/CM ²	≥ 14.0	D1709

All information, recommendations and suggestions contained herein, including, without limitations, stated values (collectively the "Information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The Information does not constitute a warranty nor guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own test. Transcendia shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the Information.

Revision Date: 10/24/2016

CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800.618.5060 | 847.678.1800 main | 847.233.0199 fax

CAN 800.268.4108 | 416.292.6000 main | 416.292.7399 fax

TRANSCENDIA.COM

© 2016 Transcendia Inc. All Rights Reserved.