

# OPTICITE® & OPTICITE® SQZ FILMS

MAKE AN IMPACT WITHOUT WORRYING  
ABOUT MOISTURE OR HUMIDITY

OPTICITE label films are used for label and pressure-sensitive applications. As North America's premier manufacturer and converter of plastic film, Transcendia provides a broad portfolio of FDA-compliant film types and thicknesses, custom converted to your specifications, along with unparalleled expertise, technical support, fast order fulfillment and low minimum order quantities. Inventory stocking programs are available from production facilities throughout the U.S. and Canada.

## OPTICITE 620 BENEFITS & FEATURES

- Moisture-resistant
- High stiffness and low tear strength—good for tamper-evident applications
- More easily die-cut than BOPP and easier to dispense/apply
- Better yield than PET
- Wide range of thickness available
- Not affected by humidity

## OPTICITE SQZ BENEFITS & FEATURES

- Conformable
- Fully squeezable, similar to flexible vinyl
- Recyclable on polystyrene and polyethylene containers
- Moisture and stain-resistant
- No shrinkage or adhesive “halo”



### PERFECT FOR:

Cleaners  
Commercial Bottles  
Health and Beauty  
Industrial

Inter-Layer Base for Peel-Off  
Labels and Booklets  
Mailing Tabs  
Wafer Seals



# OPTICITE® & OPTICITE® SQZ FILMS

CHOOSE THE OPTICITE MOISTURE-RESISTANT  
FILM THAT'S PERFECT FOR YOUR APPLICATION

Name	Description	Thickness		Width*	
		( $\mu$ m)	(mil)	(mm)	(in)
OPTICITE 620	Clear, high-gloss	32 -76	1.25 - 3.0	1015 - 2005	40 - 80
OPTICITE SQZ clear	Contact clear, medium-gloss, flexible	76	3.0	1320 -1550	52 - 61
OPTICITE SQZ white	White, satin finish, flexible	89	3.5	1020, 1335 - 1420	41.7, 52.6 - 56

**\*Master roll sizes. Not all combinations of thickness and width are available in master rolls. All slit roll widths are available.**

