

ONE STEP WALKER TALKER® FLOOR GRAPHICS

Just print, die cut and apply. Transcendia's One Step Walker Talker® Floor Graphics deliver bold, stunning graphics on a tough, slip-resistant surface that doesn't require an overlaminates. Designed for most smooth, hard surfaces, One Step Walker Talker® Floor Graphics are easy to apply and remove cleanly.

SPECIFICATIONS

- R10 slip rated
- 6.7 mil thick
- Available in slit rolls up to 60" and customized converted sheet sizes
- Adhesion after 24 hours: 16N/25mm
- Ultra-tough polyester base

BENEFITS & FEATURES

- Slip- and scratch-resistant surface
- Directly printable with all standard inks including (Eco)solvent, UV Curable and Latex, without the need to laminate. HP® Latex certified.
- Easy to apply and removes without tearing or leaving any residue
- Offers far wider color gamut vs. traditional laminated floor graphics
- Excellent toughness prevents damage from floor cleaners, pallet trucks and stiletto heels
- No shrinkage

RECOMMENDED CONDITIONS

Print Room	15°C to 30°C	30°C to 65°C
Usage	-40°C to 80°C	10°C to 90°C
Storage	10°C to 20°C	20°C to 50°C

As with all film media, this product must be allowed to "gas out" after printing. This can be achieved by leaving the prints face-up, ideally for 24 hours, to set and harden the unique-scratch resistant properties. If unable to do this, e.g. with a long print run, after printing the roll, stand it vertically and loosely unwind as much as possible to allow air in and gasses out.



PERFECT FOR USE ON MOST HARD SURFACES SUCH AS CONCRETE AND TILES AS WELL AS LOW PILE CARPET TILES

Supermarkets
Shopping Malls

Convention Centers
Airports



CORPORATE HEADQUARTERS 9201 W. Belmont Avenue | Franklin Park, IL 60131

USA 800-321-8544 | 847-678-1800 main | 847-233-0199 fax
CAN 800-268-4108 | 416-292-6000 main | 416-292-7399 fax

TRANSCENDIA.COM